

## EZ100 EZ Sensor Display



- Fully scalable for any 4-20 mA sensor
- Water resistant housing
- Battery or external powered

### Description

All Global Water electronic sensors interface to the Global EZ Sensor Display, which can be used for both portable and permanent installations. The Global EZ Display features a large LCD readout that can be configured, to display the 4-20mA electronic sensor values in any engineering units. The portable display is housed in a rugged, weatherproof enclosure that can be either hand held or wall mounted.

The Global EZ Display comes with two installation options:

- Battery powered for portable hand-held or stationary applications (when no power is available). When the button is pushed the display stays on for as long as you hold down the button.
- External 18VDC power for continuous monitoring applications. In this mode the display is on permanently and the 4-20 mA signal can be used to interface with process control systems or dataloggers.

### Specifications

*Output Range:* +1900 Engineering Units

*Input Range:* 4-20 mA

*Accuracy:* +0.05% of full scale

*Operating Voltage:* 10-36VDC

*Warm Up Time:* 1 minute

*Operating Temperature:* 0° to +60°C

*Size of Display:* 4 3/4"x3 1/8"x2 1/8"

*Weight:* 0.5 lb.

### Options and Accessories

**EZ100** Sensor Display

*Please specify power option when ordering.*

Contact  
Global Water  
for all your  
instrumentation  
needs:

Water Level

Water Flow

Water Samplers

Water Quality

Weather

Remote Monitoring

Control

### Regional Distributor



**Global Water**  
*The Leader in Water Instrumentation*

803, Riqqa Palace Building  
Al-Maktum Ave. opposite Deira Etisalat  
P.O.Box 181802 Dubai, UAE  
Tel: +9714 - 2270081  
Fax: +9714 - 2239962  
E-mail: [rscso@eim.ae](mailto:rscso@eim.ae)  
[www.rcs-co.com](http://www.rcs-co.com)

**RS**  
**Rabbit Control Systems**  
Automation & Control Engineering