

FP111 Global Flow Probe

Digital water velocity meter



- Digital display in ft/sec or m/sec
- Records 30 data sets for later analysis
- Rain-proof digital computer
- Highly accurate easy flow monitoring
- Debris shedding turbo-prop
- Lightweight, rugged, and reliable
- Telescoping handle with staff gauge
- Padded carrying case for easy storage
- CE Certified
- Used by water professionals worldwide for over 12 years
- Ideal for measuring flows in streams, rivers, canals, stormwater, wastewater and industrial process waters

Description

The Global Water Flow Probe is a highly accurate water velocity instrument for measuring flows in open channels and partially filled pipes. The water velocity probe consists of a protected water turbo prop positive displacement sensor coupled with an expandable probe handle ending in a digital readout display. The water flow meter incorporates true velocity averaging for the most accurate flow measurements. The Flow Probe is ideal for storm water runoff studies, sewer flow measurements, measuring flows in rivers and streams, and monitoring velocity in ditches and canals.

Turbo-Prop Sensor:

The Flow Probe has a unique Turbo-Prop propeller sensor that uses the positive displacement technique for velocity sensing. The Turbo-Prop is designed to shed debris and is protected inside a 2 inch diameter housing. The probe housing may be placed directly on the bottom of pipes or streambeds for measuring low flows down to 2 inches in depth. The flow meter propeller rotates freely on its shaft with no mechanical interconnections for minimal friction. The Turbo-Prop, is easily removed for cleaning or replacement.

Water Velocity Computer

The water velocity computer receives an electrical signal from the propeller, amplifies the signal, and converts the reading to feet per second (or meters per second, depending on programming). The large LCD screen displays average, minimum, and maximum water velocity readings. Up to 30 sets of time and date stamped data points can be stored in the computer with the push of a button. These data points can be reviewed on the computer screen for later analysis. The computer has a water-resistant housing and incorporates a unique four-button operation for changing functions and resetting the display. The water velocity computer is powered by a non-replaceable battery that will last approximately five years with normal use. Low battery and end of data warnings will also display as appropriate.

Flow Probe Handle

The Flow Probe handle can telescope from 3 feet to 6 feet in length (FP111) or 5 feet to 15 feet (FP211). The handle is constructed of anodized aluminum for light weight and long life. The 15 foot length of the FP211, Flow Probe, allows for measuring sewer flows from street level and measuring stream flows from low bridges. A 3-foot mylar coated staff gauge (graduated in hundredths of a foot and centimeters) is attached to the lower section of the water velocity probe for instant water depth measurements and accurate propeller positioning.

Regional Distributor



Global Water
The Leader in Water Instrumentation

803, Riqqa Palace Building
Al-Maktum Ave. opposite Deira Etisalat
P.O.Box 181802 Dubai, UAE
Tel: +9714 - 2270081
Fax: +9714 - 2239962
E-mail: rcsco@eim.ae
www.rcs-co.com

RS
Rabbit Control Systems
Automation & Control Engineering

Contact
Global Water
for all your
instrumentation
needs:

Water Level

Water Flow

Water Samplers

Water Quality

Weather

Remote Monitoring

Control



FP111 Global Flow Probe

Digital water velocity meter

Specifications

Range: 0.3-19.9 FPS (0.1-6.1 MPS)

Accuracy: 0.1 FPS

Averaging: True digital running average. Updated once per second.

Display: LCD, Glare and UV Protected

Control: 4 button

Datalogger: 30 time and date stamped data sets

Features: Timer, Low battery warning, and End of data warning

Sensor Type: Protected Turbo-Prop propeller with magnetic pickup.

Weight:

Instrument: 2 lbs. (0.9 kg) (FP111), 3 lbs. (1.4 kg) (FP211)

Shipping: 10 lbs. (4.5 kg) (FP111), 13 lbs. (5.9 kg) (FP211)

Expandable Length: 3 to 6 ft (0.9 to 1.8 m) (FP111); 5 to 15 ft (1.5 to 4.6 m) (FP211)

Materials:

Probe: PVC and anodized aluminum with stainless steel water bearing

Computer: ABS/Polycarbonate housing with polyester overlay

Power: Internal Lithium Battery, Approx 5 year life, Non-Replaceable

Operating Temp: -4° to 158° F (-20° to 70° C)

Storage Temp: -22° to 176° F (-30° to 80° C)

Carrying Case: The Flow Probe is shipped in a padded carrying case.

Approvals: CE



Options and Accessories

FP111 Flow Probe

(3' to 6' handle) including carrying case. Note pole color of shipped instrument may be different than shown

FP111-S Flow Probe

(3' to 6' handle w/swivel) including carrying case. Note pole color of shipped instrument may be different than shown



FP211 Flow Probe

(5' to 15' handle) including carrying case. Note pole color of shipped instrument may be different than shown.

FP211-S Flow Probe

(5' to 15' handle w/swivel) including carrying case. Note pole color of shipped instrument may be different than shown.



Flow Probe Replacement Parts:

BA2000 Digital Flow Computer

BG0000 Prop/Bushing/Screw Kit

00-155 FP111 Carrying Case

00-082 FP211 Carrying Case

