

## TC-3000 Tri-Meter

Measure Turbidity, Color, & Chlorine in one meter



### Description

The TC-3000 Tri-Meter is ideally suited for both low-level drinking water applications as well as monitoring high turbidity in the field. The Tri-Meter has a six-detector design with special focusing optics allowing for long-term stability over a wide range of operational conditions. The Tri-Meter uses the unique detector arrangement to measure Turbidity, Color, and Chlorine. The Tri-Meter comes in two designs: one with a tungsten lamp to meet EPA 180.1 specifications, the other comes with a IR LED emitter and meets the ISO 7027 standard. The Tri-Meter uses a tube-positioning ring to limit tube variability enabling maximum sensitivity and accuracy.

The TC-3000 Tri-Meter uses an advanced micro controller which allows for advanced calibration algorithms and support of up to 6 languages including English, French, Spanish, Japanese, Portuguese, and Italian. The instrument can record up to 4000 time and date stamped data points. The Tri-Meter is compatible with Smart Link 2 software allowing the unit to interface with a PC and download data for analysis. The Tri-Meter has an easy to use menu driven system displayed on an easy to read graphic LCD display.



- Meets ISO 7027/EPA 180.1 for Turbidity Meters
- Low Level Detection of Turbidity, Chlorine, and Color
- Programmable Auto-Shut Off
- Log up to 4000 time and date stamped recordings
- Supports Six Languages

### Specifications

#### Turbidity:

Unit of Measure: NTU, FNU, FAU, ASBC, & EBC

Range: 0-4000

Resolution: 0.01 NTU/FNU (0.00-10.99)  
0.1 NTU/FNU (110-4000)  
1 NTU/FNU (110-4000)

Reproducibility: 0.02 NTU/FNU, 0,5 FAU

#### Chlorine:

Range: 0-10 ppm

Resolution: 0.01 ppm (0-5)  
0.1 ppm (5-10)

#### Color:

Range: 0-500 CU (color units)

Resolution: 0.1 CU (0-100 CU)  
1 CU (100-500 CU)

Light Source: 860nm LED (ISO)/Tungsten (EPA), 525 nm LED, UV LED 375

Accuracy: ± 2%, 0.02 or ± 2%, ±0.5 CU or 2%

Detection Limit: 0.05 NTU/FNU, 0.02 ppm, 0.2 CU

Signal Averaging: Disabled, 2, 5, 10

Power: 9V Battery, AC Optional

Data Logging: 4000 points

Auto Shut-off: Disabled, 5, 10, 30

Response time: <5 s

Languages: English, French, Spanish, Japanese, Italian, & Portuguese

Size: 8-7/8"x4-5/8"-1-7/16" (226mmx117mmx36mm)

Weight: 3 lbs (1250g)

### Options and Accessories

#### TC-3000e Tri-Meter, EPA Version

Includes 0, 1, and 10 NTU standards, sample bottle, 4 sample tubes, DPD tablets, and extra battery.

#### TC-3000i Tri-Meter, ISO Version

#### Options

AC adapter

SMARTLink 2 Software

Liquid DPD 1A Reagent, 60mL

Liquid DPD 1B Reagent, 60mL

Liquid DPD 3 Reagent, 60mL

NOTE: DPD 1A and DPD 1B are both required to test free residual chlorine and DPD1A, DPD1B and DPD3 are required for testing total residual chlorine.

#### Regional Distributor



**Global Water**  
The Leader in Water Instrumentation

803, Riqqa Palace Building  
Al-Maktum Ave. opposite Deira Etisalat  
P.O.Box 181802 Dubai, UAE  
Tel: +9714 - 2270081  
Fax: +9714 - 2239962  
E-mail: rcsco@eim.ae  
[www.rcs-co.com](http://www.rcs-co.com)

**RS**  
Rabbit Control Systems  
Automation & Control Engineering

Contact  
Global Water  
for all your  
instrumentation  
needs:  
Water Level  
Water Flow  
Water Samplers  
Water Quality  
Weather  
Remote Monitoring  
Control