

## SP250 Quick Release Water Sampler



- Easy interface with speed control for exact sample size with no spilling
- Ideal for fast tubing changes and reduced maintenance
- Reversible motor to backflush sampling hose
- Weather resistant enclosure
- Each pump head for precision pump tubing accepts tubing sizes L/S® 13, L/S® 14, L/S® 16, L/S® 25, L/S® 17, and L/S® 18.

### Description

The quick release water sampler is ideal for sample removal from wastewater, shallow wells and surface water, including lakes, ponds, and holding pools. The water sampler is lightweight, rugged, easy to use, weather resistant, and requires minimal maintenance. The peristaltic pump is designed to take a manual sample and has the ability to back flush the sample hose once you are finished taking the sample.

#### Power

The water sampler operates using an external 12 volt DC power source that can supply at least 2 A continuous. The variable speed motor is reversible and can draw water samples at a wide range of speed.

A power cord, 10 ft (3.05 m) long, is included with each quick release water sampler. The power cord is fitted with alligator clips for easy connection to most 12-volt DC batteries, including car batteries or small 12V, 5 AH gel cells.

#### Sampling

To provide high sample integrity, the water sample only contacts the norprene and polyethylene tubing. The tubing is easily cleaned or replaced. The Masterflex easy load design and adjustable tubing retention system allow for multiple tubing sizes and for changing the tubing without removing the pump head from the drive. To avoid cross contamination or lengthy decontamination procedures simply change the inexpensive tubing between samples.

### Specifications

Enclosure: Expanded UV protected PVC (14" x 12" x 6")  
 Weight: 7.5lb (Shipping Weight 9 lb)  
 Operating Temperature: 0-70°C  
 Operating Voltage: 12V DC  
 Current Draw: 2A max  
 Sample Pump: Masterflex easy-load.  
 Pump Type: Peristaltic  
 Maximum Lift: 22'  
 Flow Rate: Variable depending on tube size and head height.  
 Back flush Rate: Same as Flow Rate.  
 Pump Tube: Uses 13,14,16, 17,18, and 25 Tubing  
 Sample Hoses: Supplied with ¼" norprene and 15' nylon reinforced polyethylene tubing with intake strainer.

### Options and Accessories

**SP250** Quick release water sampler  
 Includes ¼" tubing, 15' long pick up tube and strainer, and 10' battery cable.

Contact  
 Global Water  
 for all your  
 instrumentation  
 needs:

Water Level

Water Flow

Water Samplers

Water Quality

Weather

Remote Monitoring

Control

### Regional Distributor



**Global Water**  
 The Leader in Water Instrumentation

803, Riqqa Palace Building  
 Al-Maktum Ave. opposite Deira Etisalat  
 P.O.Box 181802 Dubai, UAE  
 Tel: +9714 - 2270081  
 Fax: +9714 - 2239962  
 E-mail: [rcsco@eim.ae](mailto:rcsco@eim.ae)  
[www.rcs-co.com](http://www.rcs-co.com)

