

WS700R Refrigerated Wastewater Sampler



- Ideal for refrigerated wastewater, industrial and environmental sampling
- Simple to operate – no programming required
- Rugged construction for harsh environments
- Meets federal, state and local wastewater regulations
- Timed and external flow pulsed composite samples
- Adjustable and repeatable sample volume
- Peristaltic pump prevents sample contamination

Specifications

Operating Temperature: 0° to +70°C

Size of unit: 27"H X 20"W X 20"D

Weight: 40lb (Shipping Weight 42lb)

Materials:

Enclosure: Expanded UV protected PVC

Bottle: 2.5 gallon Polyethylene

Pickup Hose: 15' reinforced PVC 1/4" ID polyethylene flexible tubing section with intake strainer

Pump Tubing: Norprene 1/4" ID, 7/16" OD

Sample Pump:

Flow Rate: 1000 ml per minute at a 4 foot head

Type: Peristaltic

Maximum Lift: ~20 feet

Power: Internal 12V Rechargeable Battery with AC 120 VAC adapter/charger

Standby: 3 months while still retaining enough power to run the pump to capacity

Start Delay: 16 time settings from 0 to 12 hours

Composite Interval: 15 time settings from 5 min. to 12 hours plus an External Trigger mode setting

Sample Size: 15 composite sample sizes from 50ml to 2 liters plus a Full Bottle discrete setting (Approximate sizes at 4 foot head)

External Trigger Input: 250mS minimum pulse width
Switch closure or 4-24VDC

Pulse Output: 5VDC one-second pulse
1000ohm output impedance

Bottle Switch Input: Switch closure Input
Floating read switch in bottle

Rain and Water Sensors: Optional moisture sensors or switch closure inputs

Internal Fuse: 10A Slow-Blow

Description

The WS700R Refrigerated Wastewater Sampler's state of the art water sampler controller gives you complete control over your water sampling process. With the water sample size control, you can take individual time-weighted composite samples or full-bottle discrete grab samples in a 2 gallon sample bottle. The water sample interval control allows you set the time between individual refrigerated composite samples or enable the external trigger mode for flow proportional sampling. A start delay timer allows you to start multiple WS700Rs in the field at the same time, or to delay drawing a water sample after a triggering event so that your water sample better represents the water source. An automatic 15 second backflush cycle clears any debris from the strainer and empties the water from the hose so the next refrigerated composite sample is not contaminated.

Overflow Protection

The WS700R's sample bottle is equipped with a float switch that automatically turns off the peristaltic sampling pump if the water bottle becomes full.

Flow Proportional Sampling

An external pulse type flow meter can control sample interval for true flow proportional water sampling. Global Water's Open Channel Flow Monitor has a flow-proportional output signal for triggering WS700Rs.

Options and Accessories

WS700R Refrigerated Wastewater Sampler

WSSWK Stormwater Kit

Includes CA0400 Rain Sensor, CA0500 Flow Sensor and RG333 Auto-drain Rain Gauge

Regional Distributor

Contact
Global Water
for all your
instrumentation
needs:

Water Level

Water Flow

Water Samplers

Water Quality

Weather

Remote Monitoring

Control



Global Water
The Leader in Water Instrumentation

803, Riqqa Palace Building
Al-Maktum Ave. opposite Deira Etisalat
P.O.Box 181802 Dubai, UAE
Tel: +9714 - 2270081
Fax: +9714 - 2239962
E-mail: rcsco@eim.ae
www.rcs-co.com

RS
Rabbit Control Systems
Automation & Control Engineering