

RG200 6" Rain Gauge RG600 8" Rain Gauge



Description

The 6" Rain Gauge is a durable weather instrument for monitoring rain rate and total rainfall. With minimal care it will provide many years of service. The rain gauge is constructed of high impact UV-protected plastic to provide reliable, low-cost tipping bucket rainfall monitoring. The simplicity of the rain gauge design assures trouble-free operation, yet provides accurate rainfall measurements. The unit has a 6" orifice and is shipped complete with mounting brackets and 50' of two-conductor cable. The tipping bucket sensor mechanism activates a sealed reed switch that produces a contact closure for each 0.01" or 0.2 mm of rainfall.

The Global Water 8" Rain Gauge is a rugged weather instrument for monitoring rain rate and total rainfall. With minimal care it will provide many years of services. The rain gauge was designed by the National Weather Service to provide a low-cost, reliable, industrial, tipping bucket rain gauge. Its simple design assures trouble-free operation, yet provides accurate rainfall measurements. The rainfall gauge has an 8" orifice and is shipped complete with mounting brackets and 50' of two-conductor cable. The tipping bucket sensor mechanism activates a sealed reed switch that produces a contact closure for each 0.01", 0.2 mm or 1 mm of rainfall. The rain gauge sensor can be pole mounted or bolted to a level plate.

- Simple to operate and install
- Rugged design for harsh weather
- Mounting hardware included
- UV-protected plastic or aluminum

Specifications

6" Rain Gauge

Capacity: Unlimited
Accuracy: 3% up to 4"/hr
Dimensions: 6" x 15"
Shipping Weight: 3 lbs.
Cable: 50', 2 conductors

8" Rain Gauge

Capacity: Unlimited
Accuracy: 3% up to 4"/hr; 8% up to 6"/hr.
Contact rating: 3 watts, 28 VAC, 0.25 amps., 120 VAC
Dimensions: 8" x 15"
Funnel Diameter: 8"
Shipping Weight: 8 lbs.
Cable: 50', 2 conductor

Options and Accessories

RG200 6" Rain Gauge

RG600 8" Rain Gauge

Specify 1 mm, 0.2 mm, or 0.01" per tip at time of order

RG700 4-20mA Converter Module

Pulse to current converter. 32 pulses per minute equals 20mA.

Contact
Global Water
for all your
instrumentation
needs:

Water Level

Water Flow

Water Samplers

Water Quality

Weather

Remote Monitoring

Control

Regional Distributor



Global Water
The Leader in Water Instrumentation

803, Riqqa Palace Building
Al-Maktum Ave. opposite Deira Etisalat
P.O.Box 181802 Dubai, UAE
Tel: +9714 - 2270081
Fax: +9714 - 2239962
E-mail: rcsco@eim.ae
www.rcs-co.com

RS
Rabbit Control Systems
Automation & Control Engineering