

## TFH 610 Handheld Hygro Thermometers

Digital handheld hygro thermometer pen for rapid humidity and temperature measurements.



- Robust and impact resistant
- Factory calibration certificate
- Battery charge indicator
- High accuracy
- Switchable between °C/°F
- Automatic shutoff

### Description

The TFH 610, handheld hygro thermometer, is a robust and impact resistant field meter that will allow you to measure relative humidity and temperature simultaneously. The unit is highly accurate and comes with a factory calibration certificate. The instrument's large LCD shows both humidity and temperature readings at the same time. You can choose to have it display either °C or °F. In addition to having a battery charge indicator, the hygro thermometers have an automatic shutoff feature to preserve battery power.

#### Alarm function

The TFH 610, handheld digital hygro thermometer is able to send a visible alarm when the humidity value is outside a desired range specified by you. In this case an alarm bell symbol blinks on the hygro thermometer's screen. The symbol continues to blink until you acknowledge the instrument's alarm.

#### Applications

The TFH 610, handheld digital hygro thermometer has many applications including field measurements, manufacturing, computer rooms, laboratory, storage, and environmental control.

### Specifications

#### Humidity:

Range: 0 to 100% rH

Resolution: 0.1%

Accuracy:  $\pm 2.5\%$  rH (from 10 to 90%)

#### Temperature:

Range: 32 to 122°F (0 to 50°C)

Resolution: 0.1°F or °C

Accuracy:  $\pm 0.9^\circ\text{F}$  or  $\pm 0.5^\circ\text{C}$

Sensor Type: Capacitive (Humidity), Thermistor (Temperature)

Operating Temperature: 32 to 122°F (0 to 50°C)

Storage Temperature: -13 to 140°F (-25 to 60°C)

Number of Measuring Channels: 2

Measuring Rate: 1-15 sec.

Power: Lithium button cells, 3.0 V, 1000 mAh

Battery Life: up to 5 years

Housing Material: ABS

Dimensions: 4.5x 2.1 x 0.9 inch (115 x 54 x 22mm)

Weight: 2.9oz (90g)

IP rating: IP 40

Certifications: CE

### Options and Accessories

**TFH 610** - Handheld Hygro Thermometer

**AH 600** - Calibration Kit

Includes 11.1% rH, 52.7% rH, 75.4% rH calibration standards, complete with case.

Contact  
Global Water  
for all your  
instrumentation  
needs:

Water Level

Water Flow

Water Samplers

Water Quality

Weather

Remote Monitoring

Control

### Regional Distributor



**Global Water**

*The Leader in Water Instrumentation*

803, Riqqa Palace Building  
Al-Maktum Ave. opposite Deira Etisalat  
P.O.Box 181802 Dubai, UAE  
Tel: +9714 - 2270081  
Fax: +9714 - 2239962  
E-mail: rcsco@eim.ae  
[www.rcs-co.com](http://www.rcs-co.com)

**RS**  
Rabbit Control Systems  
Automation & Control Engineering