

Ohaus® CS Compact Series

Portable Electronic Scales



APPROVALS



STANDARD FEATURES

- Superior RF protection
- Reliable, stable results
- Approvals include CE listed and FCC Class B Part 15 operation
- Large removable stainless steel weighing platform
- Low profile design
- Standard AC adapter
- Easy operation
- Low battery indicator
- Auto shut-off feature
- Overload protection
- Push-button calibration

SPECIFICATIONS

CAPACITY:

CS200: 200g
CS2000, CS2000P: 2000g
CS5000, CS5000P: 5000g

READABILITY:

CS200, CS200P: 0.1g;
CS2000, CS2000P: 1g;
CS5000, CS5000P: 2g;

OVERALL DIMENSIONS:

8.0 x 5.5 x 1.5in
(20.3 x 14.0 x 3.8 cm)

DISPLAY:

LCD 0.43 (11 mm)

ZERO RANGE:

Full capacity by subtraction

OPERATING TEMPERATURE: (OPTIMUM)

65°F to 77°F (18°C to 25°C) at 10%
to 80% relative humidity, non-condensing

POWER:

Three AA alkaline batteries (included) or AC
adapter (included)

REPEATABILITY (STD. DEV):

CS200: 0.1g
CS2000, CS2000P: 1g
CS5000, CS5000P: 2g

LINEARITY:

CS200: ±0.1g
CS2000, CS2000P: ±1g
CS5000, CS5000P: ±2g

CALIBRATION:

User calibration for keypad

STABILIZATION TIME:

3 seconds

PAN SIZE:

5.75in diameter (146.05 mm dia)

AUTO SHUT-OFF:

5 minutes no activity
(battery operation only)

WEIGHING UNITS:

g, lb:oz, Newton

WARRANTY:

One-year limited warranty

Ohaus® CL Compact Series



STANDARD FEATURES

- Basic weighing with simple 2-button keypad
- Superior RF protection
- Large weighing platform
- Stackable design with integrated shipping lock
- Low battery indicator
- Auto shut-off feature
- Mechanical and software overload protection
- External push-button calibration
- Battery (standard) or AC adapter (optional) operation

SPECIFICATIONS

CAPACITY:

CL201: 200g
CL2000: 2000g
CL5000: 5000g

READABILITY:

CL201: 0.1g
CL2000; CL5000: 1g

OVERALL DIMENSIONS:

5.5 x 1.6 x 7.9in
(14 x 4.0 x 20cm)

ZERO RANGE:

To capacity by subtraction

OPERATING TEMPERATURE: (OPTIMUM)

65°-77°F (18°-25°C)

POWER:

3 AA batteries (included)
AC adapter (optional)

LINEARITY:

CL201: +/- 0.1g
CL2000; CL5000: +/- 1g

CALIBRATION:

Digital calibration from keypad

STABILIZATION TIME:

3 seconds

WEIGHING UNITS:

g, lb:oz, ozt, dwt

PAN SIZE:

4.75in/12.0cm (diameter)

DISPLAY:

LCD (0.5in/1.2cm)

NET WEIGHT:

0.875lb/0.4kg

AUTO SHUT-OFF:

5 minutes no activity (battery operation only)

WARRANTY:

One year limited warranty