

Ohaus® Valor™ 3000 Xtreme

Compact Precision Scales



STANDARD FEATURES

- Full 304SS housing with chemical-resistant keypad
- Removable stainless steel weighing pan
- USDA approved
- Supports HACCP
- Resolutions up to 20,000d
- SmartText user interface
- Standard AC power adapter
- Bright backlit LCD display
- Convenient up-front level device

APPROVALS



SPECIFICATIONS

WEIGHING UNITS:

lb, decimal or fractional oz, lb:oz, fluid oz (of water), kg, g

MODES:

Simple weighing, percent weighing, combined zero/tare, specific gravity (S)

KEYBOARD:

Three mechanical switches (One left; Two right)

CALIBRATION:

Digital external span calibration

DISPLAY:

Seven segment, six digit, 0.78 in/20 mm high LCD with white LED backlight

DISPLAY INDICATORS:

Center of zero, stability, over/under load, weighing unit and battery status

STABILIZATION TIME:

Three seconds or less

AUTO-ZERO TRACKING:

Off, 0.5, One or three divisions

OPERATING TEMP/HUMIDITY:

32°F to 104°F (0°C to 40°C) at 10% to 95% relative humidity, non-condensing, up to 2.5 miles/4000m above sea level

POWER:

9VDC 0.5A AC wall adapter 100-120VAC, 50.60Hz (included) or four 1.5 volt "C" batteries (not included)

BATTERY LIFE:

V31XH202, V31XH2, V31XW301, V31XW3, W31XW6: 50 hours with alkaline cells
V31X3, V31X6: 120 hours with alkaline cells

DIMENSIONS (L x W x H):

8.5 in x 7.3 in x 3 in (218 mm x 186 mm x 77 mm)

PAN SIZE (L x W):

V31XH202: 4.7 in/120 mm dia.
V31XH2, V31X3, V31X6, V31XW301, V31XW3, W31XW6: 5.8 x 6.2 in/146 x 158 mm

NET WEIGHT:

V31XH202: 2.6 lb/1.2 kg
V31XH2, V31X3, V31X6: 2.9 lb/1.3 kg
V31XW301, V31XW3, W31XW6: 3.1 lb x 1.4 kg

INGRESS PROTECTION:

V31XW301, V31XW3, W31XW6: NEMA 4x/IP-65

WARRANTY:

One-year limited warranty