

Ohaus® Valor™ 5000

Compact Industrial Portion Scales



STANDARD FEATURES

- Easy to clean smooth ABS plastic housing with stainless steel construction
- NSF/USDA-AMS certified and supports HACCP compliance
- Easy to see bright backlit 5 digit LCD
- Multiple weighing units including: kg, g, lb, oz, lb: oz
- Multiple weighing modes: static weighing, positive/negative static check weighing
- Three bright LEDs, yellow, green, red, and beeper for indication in check weigh operation
- Fast stabilization with auto-tare
- Remote tare foot switch connection
- Integrated level bubble and adjustable feet
- Standard AC power adapter and internal lead acid/rechargeable battery pack
- Five level low battery detect, (low bat warning, safe shut down)
- NTEP Certified models (3,000): VP51P3, V51P6, V51P15, V51P30

APPROVALS



SPECIFICATIONS

REPEATABILITY:

V51PH3: 0.0002 kg
V51PH6: 0.001 kg
V51PH15/V51PH30: 0.002 kg
V51P3: 0.0005 kg
V51P6: 0.001 kg
V51PH15: 0.002 kg
V51PH30: 0.005 kg

LINEARITY:

V51PH3: ±0.0002 kg
V51PH6: ±0.001 kg
V51PH15/V51PH30: ±0.002 kg
V51P3: ±0.0005 kg
V51P6: ±0.001 kg
V51P15: ±0.002 kg
V51P30: ±0.005 kg

WEIGHING UNITS:

g, kg, lb, oz (decimal/fractional), lb:oz (decimal/fractional oz)

WEIGHT DISPLAY:

5-digit 19 mm high digits, 7-segment back lit LCD display (with fractional ounce and battery status indicator)

APPLICATION MODES:

Weighing, checkweighing

POWER:

9VDC 0.5A AC adapter, internal rechargeable sealed lead-acid battery

BATTERY OPERATING TIME:

120 hours

TARE RANGE:

To capacity by subtraction

OPERATING TEMPERATURE

RANGE:

-10°C to 40°C/14°F to 104°F

CONSTRUCTION:

Plastic housing and stainless steel platform

PAN SIZE (D x W):

209 x 209 mm/8.2 x 8.2 in

OVERALL DIMENSIONS (H x W x D):

5 x 8.8 x 11.8 in (10 x 223 x 300 mm)

WARRANTY:

One-year limited warranty