

NEW

Rice Lake TP Series

Tuning Fork Precision Balance



STANDARD FEATURES

- Large 16.5mm high Liquid Crystal Display (LCD)
 - Selectable modes-weight, unit count and percentage
 - 12 units of measurement
 - Mono-Metal Tuning Fork Sensor(MMTS)-provides quick response and stability
 - 20-step bar graph display
 - 115VAC adaptor included (230VAC optional)
 - One part in 620,000 resolution
 - RS-232 bidirectional
- Optional Features**
- Rechargeable battery

SPECIFICATIONS

DIMENSIONS: (W x D x H)

TP-220 - 9.2in x 7.1in x 6.6in
TP-820 - 9.2in x 7.1in x 2.9in
TP3200 - 10.1in x 7.5in x 3.4in
TP-8200 - 10.1in x 7.5in x 3.4in

PAN SIZE:

TP-220 - 4.6in
TP-820 - 6.6in x 5.5in
TP-3200 - 7in x 6.2in
TP-8200 - 7in x 6.2in

TARE:

Full weighing range

MODES:

Weighing, counting, percentage

OPERATION TEMPERATURE:

5°C to 35°C, 41°F to 95°F
80% RH or less

REPEATABILITY/STD DEV:

1 division

RS 232 SPECIFICATIONS:

Baud rate - 1200/2400/4800/9600
Data bits - 8
Connector - DIN 5 - pin

LINEARITY:

+/- 1 division

WARRANTY:

Five-year limited warranty