

Sartorius® LA Reference Series

Toploading Balances



STANDARD FEATURES

- isoCAL calibration
- Reptest
- IP54 rating
- RS-232 full-duplex interface
- GLP/GMP printout protocol
- Configured print out
- Backlit Liquid Crystal Display (LCD)*
- Number and alpha keys
- Below balance weighing**
- Applications on board: counting, checkweighing, percent, unit toggle, preset tare, animal weighing, net total, formulation, statistics, calculations, timer, differential weighing, density determination, memory (300)

* Cable length from balance to display is 1.8ft for balances with capacities ≤ 12kg and 2.6ft for all others

**Below balance weighing is a standard feature on models with capacities ≤ 12kg. For all other capacities, accessory PN 83243 is required

SPECIFICATIONS

CAPACITY:

LA2000P: 1010 | 2,000g
 LA5200D: 1010 | 5,200g
 LA220S: 220g
 LA620S: 620g
 LA1200S: 1200g
 LA620P: 120/240/620g
 LA3200D: 1,000/3,200g
 LA420: 420g
 LA820: 820g
 LA2200S: 2200g
 LA4200S: 4200g
 LA6200S: 6200g
 LA8200S: 8200g
 LA2200P: 400/800/2,200g
 LA8200P: 2,000/4,000/8,200g
 LA5200P: 1,200/2,400/3,600/5,200g
 LA2200: 2,200g
 LA4200: 4,200g
 LA6200: 6,200g
 LA12000S: 12,000g
 LA16001S: 16,000g
 LA12000P: 3,000/6,000/12,000g
 LA64001S: 64,000g
 LA34001S: 34,000g
 LA34000: 34,000g
 LA34001P: 8,000/16,000/34,000g

READABILITY:

LA2000P, LA5200D: 1 | 10mg
 LA220S, LA620S, LA1200S: 0.001g
 LA620P: 0.001/0.002/0.005g
 LA3200D: 0.001/0.01g
 LA420, LA820, LA2200S, LA4200S, LA6200S, LA8200S: 0.01g
 LA2200P, LA8200P: 0.01/0.02/0.05g
 LA5200P: 0.01/0.02/0.05/0.1g
 LA2200, LA4200, LA6200, LA12000S, LA16001S, LA64001S, LA34001S: 0.01g
 LA12000P: 0.1/0.2/0.5g
 LA34000: 1g
 LA34001P: 0.1/0.2/0.5g

REPEATABILITY:

LA2000P, LA5200D: ±1 | 10
 LA220S, LA620S, LA1200S: ± 0.001g
 LA620P: ±0.001/0.002/0.005g
 LA3200D: ±0.001/0.01g
 LA420, LA820, LA2200S, LA4200S, LA6200S, LA8200S: ±0.01g
 LA2200P, LA8200P: ±0.01/0.01/0.03g
 LA5200P: ±0.01/0.02/0.05/0.05g
 LA2200, LA4200, LA6200, LA12000S, LA16001S: ±0.05g
 LA12000P: ±0.1/0.2/0.3g
 LA64001S, LA34001S: 0.1g
 LA34000: ±0.5g
 LA34001P: ±0.05/0.05/0.1g

LINEARITY:

LA2000P, LA5200D: ±2 | 10
 LA220S, LA620S, LA1200S: ±0.002g
 LA620P: ±0.001/0.002/0.005g
 LA3200D: ±0.002/0.01g
 LA420, LA820: ±0.01g
 LA2200P, LA8200P: ±0.02/0.02/0.05g
 LA2200S, LA4200S, LA6200S, LA8200S: ±0.02g
 LA5200P: ±0.02/0.02/0.05/0.1g
 LA2200, LA4200, LA6200, LA12000S: ±0.1g
 LA12000P: ±0.1/0.1/0.5g
 LA16001S, LA34001P: ±0.2g
 LA34001S: ±0.2g
 LA64001S: ±0.5g
 LA34000: ±0.5g
 LA64001S: ±0.5g

STABILIZATION TIME:

1.5 seconds
 LA16001S, LA34000: ≤ 1 second

CALIBRATION WEIGHT:

LA220S, LA420: 200g
 LA620P, LA620S, LA820: 500g
 LA1200S, LA3200D: 1000g
 LA2200P, LA2200S, LA4200S, LA5200P, LA2200, LA4200, LA6200: 2000g
 LA6200S, LA8200S, LA8200P, LA12000P, LA12000S: 5000g
 LA16001S, LA34001S, LA34001P, LA64001S, LA34000: 10,000g

SENSITIVITY DRIFT (+10 ... +30°C):

2 10⁻⁶ except:
 LA64001S: 3 10⁻⁶
 LA12000S, LA6200, LA4200, LA2200, LA12000P: 4 10⁻⁶

PAN SIZE:

LA2000P, LA5200D, LA220S, LA620P, LA620S, LA1200S, LA3200D: 5.1 in (130mm) diameter
 LA420, LA820, LA2200P, LA2200S, LA4200S, LA5200P, LA6200S, LA8200S, LA8200P, LA2200, LA4200, LA6200, LA12000P, LA12000S: 8.6 in x 7.9 in (218 x 200mm)
 LA16001S, LA34001S, LA34001P, LA64001S, LA34000: 15.7 in x 11.8 in (400 x 300mm)

WARRANTY:

Three-year limited warranty