

## DIGI® S-T-U-V



### STANDARD FEATURES

- IP66-rated
- Platform support in each corner
- Shock resistant load cells
- Rated to 300% overload

### APPROVALS



### SPECIFICATIONS

#### RECOMMENDED EXC. VOLTAGE:

5-12VDC

#### MAX EXC. VOLTAGE:

20VAC/DC

#### OUTPUT IMPEANCE:

350 ±10Ω

#### INSULATION RESISTANCE:

500MΩ or more

#### RATED OUTPUT:

0.83mV/V ±7.5%

#### RATED INPUT:

1mV/V ±7.5%

#### LOAD CELL CABLE LENGTH:

S-S/S-T: 9ft (3m) with 14 pin connector

S-U: 18ft (5.5m) with 14 pin connector

S-V: 28ft (8.5m) with 14 pin connector

#### APPROVALS:

NTEP Certified per H-44, Class III, 5000d, CC#02-111, Measurement Canada Approved AM-5393

#### TEMPERATURE RANGE:

14°F to 104°F (-10°C to 40°C)

#### WARRANTY:

Two-year limited warranty

PART#	MODEL	CAPACITY	DIMENSIONS	WEIGHT
Carbon steel platform – stainless steel platter				
73248†	S-SL	60lb/30kg	13 in x 17 in x 3.5 in	30 lb (14 kg)
73246	S-SL	150lb/60kg	13 in x 17 in x 3.5 in	30 lb (14 kg)
73247	S-SL	300lb/150kg	13 in x 17 in x 3.5 in	30 lb (14 kg)
73250	S-TL	150lb/60kg	17 in x 21 in x 4.5 in	50 lb (23 kg)
73251	S-TL	300lb/150kg	17 in x 21 in x 4.5 in	50 lb (23 kg)
73252†	S-TL	500lb/300kg	17 in x 21 in x 4.5 in	50 lb (23 kg)
74508	S-UL	150lb/60kg	24 in x 28 in x 5 in	90 lb (41 kg)
73256	S-UL	300lb/150kg	24 in x 28 in x 5 in	90 lb (41 kg)
73257	S-UL	500lb/300kg	24 in x 28 in x 5 in	90 lb (41 kg)
76511*	S-VL	1500lb/600kg	24 in x 28 in x 6 in	130 lb (59 kg)

\* Non NTEP

† Measurement Canada Approved