


Floor/Lift Truck/Pallet/Belt Scales

RoughDeck® HE

Hostile Environment Stainless Steel Low-Profile Floor Scale

STANDARD FEATURES

- Rugged washdown design
- 304 stainless steel construction
- Rigid 304 stainless steel channel frame
- Four stainless steel, welded-seal IP67, shear beam load cells
- 20ft of SURVIVOR® EL147HE hostile environment load cell cable
- TuffSeal® JB4SS stainless steel, NEMA 4X j-box with signal trim card
- Load cells protected on all four sides
- Smooth stainless steel deck
- Four stainless steel, welded-seal IP67, shear beam load cells
- Threaded eyebolt holes for easy lifting
- Five-year limited warranty



The 6 in stainless steel channels provide superior protection for load cells and cable.



The load cells are recessed within the channel and protected on all sides. SUREFOOT supports provide a superior load introduction surface, reducing extraneous forces which might affect scale accuracy.



Remote TuffSeal JB4SS stainless steel NEMA 4X junction box with 20 ft of hostile environment load cell cable

APPROVALS



SPECIFICATIONS

APPROVALS:

NTEP Certified, CC# 92-001A9
Designed to meet or exceed H44,
5,000, 10,000 - Class III 5000d
2,000 - Class III 4000d

END LOAD CAPACITY:

100% full scale at 2,000lb and 5,000lb
80% full scale at 10,000lb

CABLE LENGTH:

20ft (6.1m)

WARRANTY:

Five-year limited warranty

BASES

PART #	SIZE (W x L x H)	CAPACITY	WEIGHT
18680*	2.5 ft x 2.5 ft x 3.5 in	2000 lb (1000 kg)	173 lb
18681*	3 ft x 3 ft x 3.5 in	2000 lb (1000 kg)	232 lb
18682	4 ft x 4 ft x 3.5 in	5000 lb (2500 kg)	375 lb
18683	4 ft x 4 ft x 3.5 in	10,000 lb (5000 kg)	490 lb
18684	4 ft x 5 ft x 3.5 in	5000 lb (2500 kg)	437 lb
18685	4 ft x 5 ft x 3.5 in	10,000 lb (5000 kg)	567 lb
18688	5 ft x 5 ft x 3.5 in	5000 lb (2500 kg)	541 lb
18689	5 ft x 5 ft x 3.5 in	10,000 lb (5000 kg)	696 lb
18693	5 ft x 7 ft x 3.5 in	10,000 lb (5000 kg)	929 lb

* Not recommended for use with pallet jacks.