

Instrumentation/Process Control

NEW

Tracer® AV

Baggage Weighing Instrumentation




STANDARD FEATURES

- Customer display (panel mount), supports two RD-1 displays
- Ticket agent keypad
- Flashes display for overweight bags

Tracer AV combines a sleek two-button keypad, to select pounds or kilograms and re-zero, with the most durable stainless steel bagwell display. The simple-to-install bagwell display has large, bright LED characters and the rugged piezo keypad will endure years of busy check-in counter use.

Tracer AV components consist of a Analog to Digital converter box, bagwell display(s) and 2-button keypad(s).

 Ideal for Aviation Weighing. A complete system can be sold with the Benchmark LP or Benchmark HD. Reference Bench Scales for specifications

APPROVALS



SPECIFICATIONS

OPERATOR KEY PAD:

Stainless steel, panel mounted,
2-keys - zero and units

CUSTOMER INTERFACE:

Stainless steel, panel mounted, 6-digit LED
display, 0.8 in digits

ENCLOSURE:

Bagwell display 7.5 x 4.0 x 0.9in
A/D converter box 10 x 5 x 2in

VOLTAGE INPUT:

115/230VAC to power supply
50-60 Hz

SERIAL COMMUNICATIONS:

RS-232 full duplex to host, up to 38.4 kbps, data
7 odd, 7 even, 8 none

REMOTE DISPLAY PORTS:

19.2 kbps, data 8 none

LOAD CELL EXCITATION:

5VDC

ANALOG RANGE:

-0.5mV/V to +4.5mV/V

A/D SAMPLE RATE:

Up to 60 per second

TEMPERATURE RANGE:

14°F to 104°F (-10°C to 40°C)

APPROVALS:

NTEP Certified 04-07645, Class III
CUL Marked

WARRANTY:

Two-year limited warranty