



STANDARD FEATURES

920i[®] HMI Controller

- Customized prompts guide operators through functions
- Real-time graphic presentation of inventory
- Graphic icons and messages show function status
- Convenient navigation pad increases efficiency and accuracy
- Large 4.6n W x 3.4n H 320 x 240 pixel, back-lit LCD
- Selectable character sizes from 0.25n to 1.2n
- Five displayed soft keys with 10 user-defined and 14 preset functions per screen
- Front panel or serial configuration/calibration
- NEMA 4X/IP66 stainless steel enclosure
- Four bidirectional communications ports
- Communication protocol cards include DeviceNet™, Allen-Bradley® Remote I/O, Profibus® DP, and Rockwell® Ethernet TCP/IP

CW Options/Accessories

- Networking
- Printing
- Sortation
- Over/under light bars
- Rejection systems
- Bar code scanners
- Touchscreen controller

SPECIFICATIONS

CONSTRUCTION:

Stainless steel or powder coated mild steel

PACKAGE WEIGHT:

Up to 200lb (90 kg)

ACCURACY:

0.01 lb (4.53 g)

SPEED:

Up to 80 products per minute

APPLICATIONS:

Logistics and distribution, food processing, industrial, and weight verification

CONTAINER TYPES:

Boxes, bags, pouches, bundles

BELTS:

Various sizes