

392 INDUSTRIAL CONDUCTIVITY TRANSMITTER



- Isolated 4-20 ma output
- Selectable Wide Measurement Range
- **Automatic Temperature Compensation**
- 1/8 DIN Mounting
- Adjustable Zero
- High 50/60 Hz Noise Rejection

Description

The industrial conductivity transmitter is a 4-wire 4-20 mA conductivity transmitter enclosed in a 1/8 DIN aluminum mounting enclosure. The industrial conductivity transmitter has an isolated 4-20 mA output with display on a large LCD screen powered by 115/230 VAC. The conductivity transmitter has selectable conductivity values from 19.99 uS/cm to 199.9 mS/cm via internal dip switch and jumper settings. The industrial conductivity transmitter uses a 10k thermistor for 5 to 55°C values for automatic temperature compensation. The industrial conductivity transmitter connections are made with terminal blocks via spade lug connectors.

Specifications

Conductivity:

Range:	Resolution:	Cell Constant:
0 to 19.99 uS/cm	0.01 uS/cm	K=0.01
0 to 199.9 uS/cm	0.1 uS/cm	K=1.0
0 to 1999 uS/cm	1.0 uS/cm	K=1.0
0 to 19.99 mS/cm	0.01 mS/cm	K=1.0
0 to 199.9 mS/cm	0.1 mS/cm	K=10

Range: Selectable via dipswitch and jumper

Accuracy: +1% of Span + 1 Digit ATC: 5-55°C +2%/ °C, 10k Thermistor

Output: 4-20mA (Isolated)

Load: 450 ohms

Isolation to GND: 500 VDC Input Impedance: >1012 ohm Operating Temperature: 5-45°C

Power Source: 115 to 230 VAC +15%, 50/60Hz

Mounting: 1/8 DIN Aluminum Case

Contact **Global Water** for all your instrumentation needs: Water Level Water Flow

Water Samplers

Water Quality

Weather **Remote Monitoring**


Control

Options and Accessories

392 Industrial Conductivity Transmitter (Conductivity sensor not included)

392-120 Industrial Conductivity Sensor SS probe, Platinum, K=1.0, 0 to 1000 uS, 10-ft cable, ABS Plastic Body, 3/4 in MNPT mounting, Tinned Leads

Regional Distributor





803, Rigga Palace Building Al-Maktum Ave. opposite Deira Etisalat P.O.Box 181802 Dubai, UAE

Tel: +9714 - 2270081 Fax: +9714 - 2239962 E-mail: rcsco@eim.ae www.rcs-co.com

