

WQ301 Conductivity Sensor

Rugged Water Conductivity Sensor



Features

- Measure conductivity at any depth
- Fully encapsulated electronics
- 4-20 mA output
- Marine grade cable with strain relief
- Stainless steel housing

Applications



Ideal for stream and lake monitoring, aquaculture studies, baseline analyses, mitigation monitoring, and other environmental applications.

Description

Global Water's WQ301 Conductivity Sensor is a rugged and reliable water conductivity measuring device. The WQ301 offers a rapid and non-destructive way to measure the ion content in a solution. The conductivity sensor is molded to 25' of marine grade cable, with lengths up to 500' available upon request. The conductivity sensor's output is 4-20 mA with a three wire configuration. The unit's electronics are completely encapsulated in marine grade epoxy within a stainless steel housing.

Record and Control

As with all of Global Water's 4-20 mA output sensors, you can add recording and controlling capabilities to the WQ301 Conductivity Sensor with the GL500 Datalogger and PC300 Controller. The GL500 connects to the conductivity sensor's 4-20 mA output to record data. Global Water's PC300 Controller connects to the conductivity sensor's output to control pumps or alarms.

Specifications

Output	4-20 mA
Ranges	0 to 500, 0 to 2,000, 0 to 5,000, 0 to 10,000, 0 to 20,000, 0 to 40,000 μ S
Accuracy	1% full scale
Maximum Pressure	50 psi
Operating Voltage	12 VDC (\pm 5%)
Current Draw	0.8 mA plus sensor output
Warm-up Time	3 seconds minimum
Operating Temperature	-40° to +55°C
Temperature Compensation	2% per °C
Electrodes	316 stainless steel
Size of Probe	Open Water: 1" dia. x 12" long (3.175cm dia. x 30.5cm) Online: 2.5" dia. x 15.5" long (6.35cm dia. x 39.4cm)
Weight	Open Water: 8 oz (227 g) Online: 22 oz (624 g)

Ordering & Options

Conductivity Sensors for Open Water¹

Order No.	Conductivity Range (μ S)
WQ301A	0 to 5,000
WQ301B	0 to 10,000
WQ301C	0 to 20,000
WQ301D	0 to 2,000
WQ301E	0 to 40,000
WQ301F	0 to 500

1) Sensors include 25' of cable.

Online Conductivity Sensors²

Order No.	Conductivity Range (μ S)
WQ301A-O	0 to 5,000
WQ301B-O	0 to 10,000
WQ301C-O	0 to 20,000
WQ301D-O	0 to 2,000
WQ301E-O	0 to 40,000
WQ301F-O	0 to 500

2) Online sensors include 1-1/4" NPT thread and 25' of cable.

Cable

Order No.	Description
WQEXC	Extra Sensor Cable, per foot (up to 500')

Please call us for calibration standards.



Global Water
The Leader in Water Instrumentation

803, Riqqa Palace Building
Al-Maktum Ave. opposite Deira Etisalat
P.O.Box 181802 Dubai, UAE
Tel: +9714 - 2270081
Fax: +9714 - 2239962
E-mail: rcsco@eim.ae
www.rcs-co.com

RS
Rabbit Control Systems
Automation & Control Engineering

Regional Distributor