

Acculab® ECON Series



STANDARD FEATURES

- Unique low-cost design
- Stackability (units can be stacked for safe convenient storage)
- Microprocessor controlled
- Lock down capability
- Five weighing modes; g, oz, lb, ozt, dwt
- 9V battery operation included (optional AC operation)
- Six minute auto off (saves battery life)
- Overload/Underload and low battery indicators
- External "one button" digital calibration
- Transportation lock (protects weight cell from damage)
- Backlit LCD/0.35in segment height

SPECIFICATIONS

LINEARITY:

EC-211, EC-411, EC-2100: ± 2 d
EC-4100: ± 3 d

PAN SIZE:

5.3in x 5.5in
(135mm x 140mm)

DIMENSIONS (W x D x H):

6.26in x 8.6in x 2.07in
(159mm x 218mm x 53mm)

WARRANTY:

One-year limited warranty

Acculab® Pocket Pro Series



STANDARD FEATURES

- Calibration weight and tray included with all models
- Blue back-lit display for easy viewing in all ambient conditions
- Scales weigh in "grams & ounces" (PP-62 features grams, ounces, grains and carats)
- Battery operation (one AA battery included)
- Auto of (saves battery life)
- Overload/underload and low battery indicators
- External "one button" calibration with included weight
- Display 0.35in segment height

SPECIFICATIONS

LINEARITY:

PP-62: ± 3 d
PP-201, PP-401: ± 2 d

REPEATABILITY:

PP-62: ± 2 d
PP-201, PP-401: ± 1 d

WEIGHING MODES:

Grams, ounces, grains, carats

CALIBRATION:

PP-62: 50g
PP-201: 100g
PP-401: 200g

STABILIZATION TIME (TYPICAL):

PP-62: 3 seconds
PP-201, PP-401: 2 seconds

OPERATING TEMPERATURE:

50°F-86°F (10°C-30°C)

STORAGE TEMPERATURE:

14°-158°F (-10°C-70°C)

OPERATING HUMIDITY:

Less than 80% RH

LOW BATTERY INDICATION:

"Lo" on LCD display

POWER REQUIREMENTS:

One AA battery (included)

POWER CONSUMPTION:

25mA, 40mA with backlight

PAN SIZE:

2.9in x 2.5in (73mm x 63mm)

DIMENSIONS (W x D x H):

2.9in x 3.5in x 0.875in
(74mm x 89mm x 22mm)

NET WEIGHT:

0.24lbs (0.12kg)

WARRANTY:

One-year limited warranty