

Acculab® Exceleron Series



STANDARD FEATURES

- Large back-lit Liquid Crystal Display (LCD)
- Maximum displayedesolution; 1:15000 digits
- 6 key function tactile keybodr
- Stainless steel column
- ABS Industrial Indicator
- Battery operation
- Level indicator
- Leveling feet
- RoHS/Wee compliant
- User defined calibration weight value

Optional Features

- Casters/wheels available (M12)
- Wall mounting bracket
- Table bracket
- Bidirectional RS-232

SPECIFICATIONS

PAN SIZE:

6kg - 60kg: 15.75in x 11.8in 150kg: 19.7 in x 15.75 in 300 kg: 25.6 in x 19.7 in

COLUMN HEIGHT:

6kg - 60kg: 19.7in 150kg, 300kg: 29.5in

LINEARITY:

6kg - 60kg: +/- 1.0g or 0.005lbs 150kg: +/- 20.0g or 0.05lbs 300 kg: +/- 40.0 g or 0.1 lbs

REPEATABILITY:

6kg - 60kg: +/- 1.0g or 0.005lbs 150 kg: +/- 20.0 g or 0.05 lbs 300 kg: +/- 40.0 g or 0.1 lbs

TARE:

Full weighing range

MODES:

Weighing, counting, check weighing, unit toggling (lbs, kg, grams, ounces)

OPERATING TEMPERATURE:

-10°C - 40°C (14°F - 104°F)

OPERATING HUMIDITY:

85% relative humidity

POWER REQUIREMENTS:

No AC adaptor, power cord is directly wired 120 V 50/60 Hz

WARRANTY:

Two-year manufacturer warranty





