Ohaus® Valor™ 2000

Compact Washdown Scales



APPROVALS







STANDARD FEATURES

- Unsurpassed potection and durability in a variety of harsh environments
- High profile, easy-to-clean plastic housing
- NEMA-4X/IP-65 potection rating
- Front and ear LEDS
- Multiple weighing units
- Internal rechargable battery (standal)
- Removable stainless steel platform cover
- **USDA-AMS** accepted
- NSF listed/certified
- Supports HACCP systems
- User adjustable stability settings
- One-second esponse time
- SmarText interface

SPECIFICATIONS

APPROVABLE READABILITY (g):

2.125

WEIGH UNITS:

Kilograms, pounds, grams, ounces

MODES:

Weigh

KEYBOARD:

Two mechanical kevs

CALIBRATION:

Digital external span calibration

DISPLAY TYPE:

2x red LED (front and rear) six digit, seven-segment, 15 mm/0.6 in characters

DISPLAY INDICATORS:

Units of measure, stability, battery charge status

STABILIZATION TIME:

<=one seconds

AUTO ZERO TRACKING:

User selectable from 0.1 d to 3 d

OPERATING TEMP RANGE:

32°F to 104°F (0°C to 40°C)

OPERATING HUMIDITY RANGE:

10% to 95% relative humidity non-condensing, up to 2.5 miles/4000 m above sea level

POWER:

9VDC 0.7A AC adapter (included) Internal rechargeable sealed lead acid battery

TYPICAL BATTERY LIFE:

40 hours with 12 hour recharge time

CONSTRUCTION:

ABS plastic housing, stainless steel pan

SAFE OVERLOAD:

120% of capacity

SCALE DIMENSIONS:

233w x 249d x 142h/ 9.2 w x 9.8d x 5.6h

PAN SIZE:

233 x 184/9 2 x 7 2

PROTECTION RATING:

NEMA 4x/IP-65

WARRANTY:

One-year limited warranty







