BenchMark™ SL, CW-80B, HE Series **Light-Capacity Bench Scales**



APPROVALS



STANDARD FEATURES

- 304 stainless steel construction
- $\mbox{LifeGuad} \ ^{\text{\tiny TM}} \ \mbox{base design isolates load cell from overloads and } \\$ shock loads for added durability
- Specially designed adjustable support feetpoide exceptiona traction and won't scratch surfaces

SL Series additional features

NTEP Certified aluminum load cell

CW-80B Series additional features

NTEP Certified stainless steel load cell

HE Series additional features

NTEP Certified stainless steel, hermetically sealed load cell

SPECIFICATIONS

LOAD CELL, NTEP - CERTIFIED:

SL Series: Aluminum and environmentally sealed CW-80B: Stainless steel and environmentally sealed IP67

HE Series: Stainless steel, hermetically sealed IP69

OUTPUT IMPEDANCE:

SL and CW-80B: 350 ohms HE: 1000 ohms

MAXIMUM OVERLOAD:

200%, except 150% for 30 lb HE version

OVERLOAD PROTECTION:

Shock-absorbing spider

CABLE LENGTH:

10ft (3m)

COMPENSATED TEMPERATURE RANGE:

14°F to 104°F (-10°C to 40°C)

APPROVALS:

SL and HE Series: NTEP Certified per H-44, Class III, 5000d, CC #95-072A2

Measurement Canada approved, AM-5082 CW-80B: NTEP Certified per H-44, Class III, 3000d, CC# 96-107 Measurement Canada approved, AM-5156

WARRANTY:

SL and CW-80B: Two-year limited warranty HE: Three-year limited warranty including

DIMENSIONS							
PART# (SL)	PART# (CW-80B)	PART # (HE)	CAPACITY	PLATFORM SIZE (L X W)	L1/W1	H (SL & CW-80B)	H (HE)
18575*	N/A	N/A	2 lb (1 kg)	10in x 10in	10.25 in	3.15in	3.58 in
18576	N/A	86942	5 lb (2.5 kg)	10in x 10in	10.25 in	3.15in	3.58 in
N/A	35075	N/A	6 lb (3 kg)	10 in x 10 in	10.25 in	3.15in	N/A
18577	35076	86943	10lb (5kg)	10 in x 10 in	10.25 in	3.15 in	3.58 in
N/A	35077	N/A	15lb (7kg)	10 in x 10 in	10.25 in	3.15 in	3.58in
18578	N/A	86944	20lb (10kg)	10 in x 10 in	10.25 in	3.15 in	3.58in
18579	35078	86945	30lb (15kg)	10 in x 10 in	10.25 in	3.15 in	3.58in
32914	35079	86946	30 lb (15 kg)	12 in x 12 in	12.25 in	3.25 in	3.63 in
32913	N/A	86947	50 lb (25 kg)	12 in x 12 in	12.25 in	3.25 in	3.63 in
N/A	35080	N/A	60 lb (30 kg)	12 in x 12 in	12.25 in	3.25 in	3.63 in
35198	N/A	86948	100 lb (50 kg)	12in x 12in	12.25 in	3.25 in	3.63 in

*Non-NTEP Note: 1"=25.4 mm









