

Intercomp TL 6000



STANDARD FEATURES

- Aluminum or stainless steel construction
- Peak hold feature
- Self contained display
- Optional wireless or hardwire readouts

APPROVALS



SPECIFICATIONS

CONSTRUCTION:

Aluminum construction for 10,000lb and below capacities
Stainless steel construction above 10,000lb capacities

ACCURACY:

+/- 0.1% of applied load or +/-1 graduation; whichever is greater
+/- 0.2% or +/-2 graduations for 25,000 and higher

DISPLAY:

Five digit, 1.2in (30mm) high LCD

CONTROL KEYS:

On/Off, Zero (100%), Tare (100%), Peak Hold and Mode

ANNUNCIATOR:

Low Battery, Peak Hold, Set Points 1 & 2, lb, kg, tons, metric tons and dekaNewtons

POWER:

Two (9V) batteries (batteries included)

OPERATING TIME:

Up to 300 hours of continuous use. Wireless remote control models have reduced operating time of 50 hours.

OPERATING TEMPERATURE:

-4°F to 140°F (-20°C to 60°C)

ENCLOSURE:

NEMA 4X/IP 65

OVERLOAD:


200% safe, 500% ultimate

CALIBRATION:

Digital keypad, multi-point

OUTPUT:

RS-232 and RS-485



DIMENSIONS

Part#	Capacity	Resolution	A	B	C	D	E	F	G	Shackle Type/Capacity
82490	500lb (250kg)	0.5lb (0.2kg)	13in (304mm)	0.81in (21mm)	7.42in (178mm)	1in (25mm)	1.69in (43mm)	2in (51mm)	4.75in (121mm)	G-2130-3 1/4 T
82491	1000lb (500kg)	1lb (0.5kg)	13in (304mm)	0.81in (21mm)	7.42in (178mm)	1in (25mm)	1.69in (43mm)	2in (51mm)	4.75in (121mm)	G-2130-3 1/4 T
82492	2,000lb (1,000kg)	2.0lb (1kg)	13in (304mm)	0.81in (21mm)	7.42in (178mm)	1in (25mm)	1.69in (43mm)	2in (51mm)	4.75in (121mm)	G-2130-3 1/4 T
82493	5,000lb (2,500kg)	5lb (2kg)	13in (304mm)	0.81in (21mm)	7.42in (178mm)	1in (25mm)	1.69in (43mm)	2in (51mm)	4.75in (121mm)	G-2130-3 1/4 T
82494	10,000lb (5,000kg)	10lb (5kg)	15.22in (386mm)	1.06in (27mm)	7.6in (193mm)	1.4in (36mm)	2.28in (58mm)	2.77in (56mm)	5in (127mm)	G-2130-6 1/2 T
82495	25,000lb (12,500kg)	20lb (10kg)	20.9in (530mm)	1.69in (43mm)	8.7in (212mm)	2.13in (54mm)	3.63in (92mm)	4.3in (109mm)	5in (127mm)	G-2130-13 1/2 T
82496	50,000lb (25,000kg)	50lb (20kg)	24.7in (627mm)	2.06in (52mm)	9.2in (234mm)	2.44in (62mm)	5in (127mm)	5.93in (151mm)	5in (127mm)	G-2130-25 T
82497	100,000lb (50,000kg)	100lb (50kg)	29.49in (749mm)	2.81in (72mm)	10.69in (271mm)	3.88in (99mm)	7.25in (184mm)	9.4in (240mm)	5in (127mm)	G-2130-55 T
82498	160,000lb (80,000kg)	200lb (100kg)	32.6in (828mm)	2.81in (72mm)	10.69in (271mm)	3.88in (99mm)	7.88in (200mm)	7.8in (198mm)	5.4in (138mm)	G-2140-85 T
82499	220,000lb (110,000kg)	200lb (100kg)	38.4in (975mm)	3.5in (89mm)	12.4in (315mm)	4.45in (113mm)	7.88in (200mm)	8.5in (215mm)	5.9in (150mm)	G-2140-120T
82500	350,000lb (175,000kg)	500lb (200kg)	44in (1118mm)	4.5in (114mm)	15in (381mm)	5.25in (133mm)	10in (254mm)	8.88in (225mm)	7in (178mm)	G-2140-175 T
82501	400,000lb (200,000kg)	500lb (200kg)	47.8in (1118mm)	5in (127mm)	16.57in (421mm)	7in (178mm)	11in (279mm)	9.37in (237mm)	7in (197mm)	G-2140-200 T
82502	500,000lb (250,000kg)	500lb (200kg)	62.55in (1588mm)	5.25in (133mm)	18.07in (459mm)	8.75in (222mm)	13in (330mm)	17.88in (454mm)	8.45in (215mm)	G-2140-250 T

* Dimensions are top to bottom shackle eye to eye on 25-50 ton/12.5-25 metric ton capacity models

†Unit comes standard with top shackle & bottom swivel hook. Capacities to 300 tons available upon request.