

Floor/Lift Truck/Pallet/Belt Scales

RoughDeck® FXB

Flexure Lever Floor Scale



APPROVALS



SPECIFICATIONS

APPROVALS:

NTEP Certified, CC# 95-062,
Class III 5000d

ELECTRICAL:

Excitation: 10VDC - 15VDC max
Nonlinearity: .03% FS
Hysteresis: .02% FS
Bridge resistance: 350 ohms
Output: 3.0mV/V

DIMENSIONS

FXB BASES	PART #	CAPACITY	SIZE (L x W x H)	WEIGHT
FXB-1824-.5K	33134	.500lb (250kg)	18in x 24in x 6.62in.....	125lb
FXB-1824-1K	33066	1,000lb (500kg)	18in x 24in x 6.62in.....	125lb
FXB-1830-1K	33136	1,000lb (500kg)	18in x 30in x 6.62in.....	133lb
*FXB-2424-.5K	33067	.500lb (250kg)	24in x 24in x 6.62in.....	151lb
*FXB-2424-1K	33068	1,000lb (500kg)	24in x 24in x 6.62in.....	151lb
*FXB-3030-.5K	33138	.500lb (250kg)	30in x 30in x 6.62in.....	191lb
*FXB-3030-1K	33069	1,000lb (500kg)	30in x 30in x 6.62in.....	191lb
*FXB-3030-1.5K	33139	1,500lb (750kg)	30in x 30in x 6.62in.....	191lb
*FXB-3030-2K	33070	2,000lb (1000kg)	30in x 30in x 8.25in.....	281lb
*FXB-3636-1K	33140	1,000lb (500kg)	36in x 36in x 8.25in.....	234lb
*FXB-3636-2K	33071	2,000lb (1,000kg)	36in x 36in x 8.25in.....	234lb
*FXB-3636-5K	33072	5,000lb (2,500kg)	36in x 36in x 8.25in.....	234lb
*FXB-3846-1K	33141	1,000lb (500kg)	38in x 46in x 8.25in.....	610lb
*FXB-4848-2K	33073	2,000lb (1,000kg)	48in x 48in x 8.25in.....	654lb
*FXB-4848-5K	33074	5,000lb (2,500kg)	48in x 48in x 8.25in.....	654lb
*FXB-4848-10K	33075	10,000lb (5,000kg)	48in x 48in x 9.25in.....	735lb
FXB-4848-20K	33076	20,000lb (10,000kg)	48in x 48in x 13.25in.....	1115lb
*FXB-4860-5K	33077	5,000lb (2,500kg)	48in x 60in x 8.25in.....	764lb
*FXB-4860-10K	33078	10,000lb (5,000kg)	48in x 60in x 9.25in.....	845lb
*FXB-4872-5K	33149	5,000lb (2,500kg)	48in x 72in x 9.25in.....	1120lb
*FXB-4872-10K	33080	10,000lb (5,000kg)	48in x 72in x 9.25in.....	1120lb
FXB-4872-20K	33150	20,000lb (10,000kg)	48in x 72in x 13.25in.....	1600lb
*FXB-6060-5K	33081	5,000lb (2,500kg)	60in x 60in x 8.25in.....	967lb
*FXB-6060-10K	33082	10,000lb (5,000kg)	60in x 60in x 9.25in.....	1180lb
FXB-6060-20K	33152	20,000lb (10,000kg)	60in x 60in x 13.25in.....	1674lb
*FXB-6072-10K	33083	10,000lb (5,000kg)	60in x 72in x 10.25in.....	1290lb
*FXB-6084-10K	33156	10,000lb (5,000kg)	60in x 84in x 13.25in.....	1400lb
FXB-6084-20K	33157	20,000lb (10,000kg)	60in x 84in x 13.25in.....	1900lb
*FXB-7296-10K	33159	10,000lb (5,000kg)	72in x 96in x 13.25in.....	1820lb
FXB-7296-20K	33160	20,000lb (10,000kg)	72in x 96in x 15.25in.....	2340lb
FXB-84108-20K	33163	20,000lb (10,000kg)	84in x 108in x 15.25in.....	2928lb
FXB-96120-30K	33166	30,000lb (15,000kg)	96in x 120in x 19.50in.....	5600lb

* NTEP Certified



Regional Distributor

803, Riqqa Palace Building, Al-Maktum Ave. P.O.Box 181802 Dubai, UAE

Tel.: +97 14 2270081 Fax: +97 14 2239962 rcsco@eim.ae www.rcs-co.com

STANDARD FEATURES

- Unique flexure design filters motion and shock loading
- Spring steel flexures
- Rugged all-steel construction
- One Rice Lake Weighing Systems brand RL20000 series nickel-plated S-beam load cell and plated wire rope
- NTEP Certified models in sizes 24x 24in (500lb) through 72in x 96in up to 10,000lb capacity
- Two-year limited warranty

SAFE OVERLOAD CAPACITY:

150% of scale capacity

WARRANTY:

Two-year limited warranty



Commitment Beyond Measurement®