

# Instrumentation/Process Control

## 720i™

## Programmable HMI Indicator/Controller



Panel Mount  
(CPU Enclosure Not Shown)



Universal



### STANDARD FEATURES

- LCD display size: panel mount (3.8 x 1.2in)  
universal (5.3 x 1.5in)
- Four soft keys
- Truck in/out, 1,000-ID memory
- Process control engine Pro Action PCE define conditions and actions
- Data storage onboard, Pro Action DBE user defined
- (Eight Digital I/O (expandable)
- One option slot for pluggable options
- (20) Auxiliary print formats
- Time & date
- Audit trail tracking and alibi storage
- Peak hold
- Rate of change
- Accumulator
- Multi-range/interval
- Local/remote
- Two full duplex serial ports
- One PS-2 keyboard port
- Header for fiber optic, Ethernet or USB

### APPROVALS



### SPECIFICATIONS

#### POWER:

Line voltages: 115 or 230VAC,  
Frequency: 50 or 60Hz  
Power consumption: 25 watts maximum

#### EXCITATION VOLTAGE:

10VDC, 16 x 350Ω or 32 x 700Ω load cells

#### ANALOG SIGNAL INPUT RANGE:

-10mV to +45mV

#### ANALOG SIGNAL SENSITIVITY:

0.3μV/graduation minimum @ 7.5Hz  
1.0μV/graduation typical @ 120Hz  
4.0μV/graduation typical @ 960Hz

#### A/D SAMPLE RATE:

7.5 to 960Hz, software selectable

#### RESOLUTION:

Internal resolution: 8 million counts/8,000,000  
23 bit  
Weight display resolution: 9,999,999

#### SYSTEM LINEARITY:

± 0.01% full scale

#### DIGITAL I/O:

Eight channels on CPU board; optional  
24-channel I/O

#### CIRCUIT PROTECTION:

RFI, EMI, ESD protection

#### SERIAL PORTS:

Two ports on CPU board support up to 115,200  
bps; optional dual-channel serial expansion  
boards available

Port 2: Full duplex RS-232 with handshaking

Port 4: Full duplex RS-232, simplex 20A output  
PS-2 Keyboard port hard wired (Scan Code 1)

#### OPTIONAL COMMUNICATION:

Ethernet TCP/IP  
RS-485-4 wire  
Fiber optic  
USB

#### DISPLAY:

Viewable area:  
Panel mount 3.8in x 1.2in (96mm x 30mm)  
Universal 5.3in x 1.5in (133mm x 39mm)  
240 x 64 pixel, Transflective VGA Liquid Crystal  
Display (LCD) module with adjustable contrast

#### KEYBOARD:

10-key (panel mount) membrane panel,  
22-key (universal mount) membrane  
panel tactile feel,  
720i will support an external keyboard

#### OPERATING TEMPERATURE:

Legal: 14°F to 104°F (-10°C to +40°C)  
Industrial: 14°F to 122°F (-10°C to +50°C)

#### DIMENSIONS (W X H X D):

Universal: 10.5in x 7.5in x 3.4in  
Panel Mount Display: 7.6in x 3.9in x 1.5in  
CPU: 6in x 11in x 2.2in

#### WEIGHT:

Universal enclosure: 9.5lb (4.3kg)  
Panel Mount enclosure: 8.5lb (3.9kg)

#### RATING/MATERIAL:

NEMA 4X/IP66, stainless steel

#### APPROVALS:

NTEP - certified at 10,000 divisions, Class III/III  
CC# 08-022

Measurement Canada-10,000  
divisions, Class III/IIIHD (Pending)  
OIML-6,000/10,000 divisions (Pending)

CE marked  
UL /CUL listed (universal)  
UL recognized (panel mount)  
ROHS compliant

#### WARRANTY:

Two-year limited warranty