Dynamic In-Motion Precision Checkweigher



STANDARD FEATURES

Touchscreen Controller

- Large 12.1in color touchsæen
- Web enabled (emote toubleshooting)
- Multiple level password parameter menu
- Full digital font panel calibration
- Softwae-based operating system for maximum flexibility
- Graphical statisticeports
- Three or five zone sorting
- Selectable display units in g, lb, oz and kg

CR1 Options/Accessories

- Networking
- **Printers**
- 920i° HMI controller
- Metal detection
- Timing scews
- Rejection systems
- Over/under light bars
- Bar code scanners
- Washdown-rated
- Custom communications
- Caster kits

SPECIFICATIONS

APPLICATIONS:

Industrial and washdown food processing in a high speed, high throughput environment

CONFIGURATIONS:

Dual chains

CONSTRUCTION:

Stainless steel or powder coated mild

PACKAGE SIZE:

1.5 in L x 1.5 in W to 10 in L x 10 in W (3.81 cm x 3.81 cm to 25.4 cm x 25.4 cm)

PACKAGE WEIGHT:

0.176 oz to 15lb (5 q to 6.8 kg)

ACCURACY:

From .0176 oz (0.5 grams)

SPEED:

Up to 300 products per minute

CONTAINER TYPES:

Boxes, trays, tubs, cups, cans, bottles, jars

NOMINAL BELT HEIGHT:

36 in (91.44 cm) Custom heights are available





