

## Flow Probes - FP111, FP211, and FP311

DIGITAL HANDHELD WATER VELOCITY METERS

FP111

## Highly-accurate, easy flow monitoring for surface water, stormwater, wastewater, and other open flowing water sources.

The **FP111, FP211, and FP311 Flow Probes** are highly accurate water velocity instruments for measuring flows in open channels and partially filled pipes. The water velocity probe consists of a protected water turbo prop positive displacement sensor coupled with an expandable probe handle ending in a digital readout display. The water flow meter incorporates true velocity averaging for the most accurate flow measurements.



Records 30 data sets, and readings are in feet or meters per second.



Telescoping handles ranging from 3 feet to 14 feet



Rain-proof digital computer and display with 5 year shelf life

Lightweight, rugged and reliable



a xylem brand

## Flow Probes FP111, FP211, FP311







## Flow Probe Specifications

| now nobe specifications |  |
|-------------------------|--|
| Range                   | 0.3 - 19.9 FPS (0.1 - 6.1 MPS)   |
| Accuracy                | 0.1 FPS  |
| Averaging               | True digital running average. Updated once per second.   |
| Display                 | LCD, Glare, and UV Protected   |
| Control                 | 4 button   |
| Datalogger              | 30 sets, MIN, MAX, and AVG   |
| Features                | Timer, Low battery warning   |
| Sensor Type             | Protected Turbo-Prop propeller with magnetic pickup.   |
| Weight                  | Instrument: 2 lbs (0.9 kg) (FP111); 3 lbs (1.4 kg) (FP211); 2.8 lbs (1.3 kg) (FP311)                           |
|                         | Shipping: 13 lbs (5.9 kg) (FP111); 23 lbs (10.4 kg) (FP211); 19 lbs (8.6 kg) (FP311)                           |
| Expandable Length       | 3.7 to 6 ft (1.1 to 1.8 m) (FP111); 5.5 to 14 ft (1.7 to 4.3 m) (FP211); 2.5 to 5.5 ft (0.76 to 1.7 m) (FP311) |
| Materials               | Probe: PVC and anodized aluminum with stainless steel water bearing  |
|                         | Computer: ABS/Polycarbonate housing with polyester overlay   |
| Power                   | Internal Lithium Battery, Approx 5 years life with typical use, Non-Replaceable                                |
| Auto Shutoff            | After 5 minutes of inactivity  |
| Operating Temperature   | -4 °F to 158 °F (-20 °C to 70 °C)  |
| Storage Temperature     | -22 °F to 176 °F (-30 °C to 80 °C)   |
| Carrying Case           | The Flow Probe is shipped in a padded carrying case.   |
| Certificates            | CE   |



YSI, a Xylem brand 1725 Brannum Lane Yellow Springs, OH 45387

© 2020 Xylem, Inc. XA00147 1220

Section 2018
Sect

Who's Minding <sup>the</sup> Planet?<sup>°</sup>



YSI.com/Flow-Probe